



Pass

Test Time : 2/14/2024 12:35:18 PM
Project : fo1
Profile : MM Fiber NSA
Operator : Default
Jumper Method : One Jumper
Main Adapter : PROBE FIBER Hybrid MM, S/N: 2020
Cable Type : Generic MMF
Connector : LC
Configuration : Loopback
Length(m) : 31.00
No. End Connectors : 2
No. Connectors : 0
No. Splices : 0

Limit : TIA-568.3-E MultiMode REF Grade
Model : NSA
Serial Number : Main: 4200-0044
Device Software : Main: 4.2.308
Calibration Date : Main: 5/4/2021
Remote Adapter :
Cable Manufacturer : Generic
Connector Manufacturer : Generic
Set Reference Date : 2/14/2024 12:28:50 PM
Delay(ns) : 154.4
End Connector Loss : 0.5
Connector Loss : 0.75
Splice Loss : 0.3
Performance Grade : OM4

850 nm

Pair	Result	Loss	Limit	Margin
Fiber 1 Main to Remote	Pass	0.24	1.09	0.85
Fiber 2 Remote to Main	Pass	0.24	1.09	0.85

Unit	Reference Power
Main	-21.88

1300 nm

Pair	Result	Loss	Limit	Margin
Fiber 1 Main to Remote	Pass	0.24	1.05	0.81
Fiber 2 Remote to Main	Pass	0.24	1.05	0.81

Unit	Reference Power
Main	-23.19

Compliant Network

1 Gbit/s FC	1000BASE-LX
1000BASE-SX	100BASE-FX
100GBASE-SR10	100GBASE-SR4
10BASE-FLand FB	10GBASE-LRM
10GBASE-LX4	10GBASE-SR
10GBASE-SR/SW	16 Gbit/s FC
2 Gbit/s FC	32 Gbit/s FC
4 and 16 Mbit/s Token Ring	4 Gbit/s FC
40GBASE-SR4	8 Gbit/s FC
ATM at 155 Mbit/s	ATM at 52 Mbit/s
ATM at 622 Mbit/s	ControlNET
FDDI PMD	Fibre Channel (FC-PH) at 1062Mbit/s
FOIRL	